



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

Address: COMMISSIONER FOR PATENTS

P.O. Box 1450

Alexandria, Virginia 22313-1450

www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/806,242	03/24/2004	Russ Markhovsky	2437.0040000	2493
54089 7590 08/07/2008 BARDMESSER LAW GROUP, P.C. 910 17TH STREET, N.W. SUITE 800 WASHINGTON, DC 20006				
EXAMINER				
BEAMER, TEMICA M				
ART UNIT		PAPER NUMBER		
2617				
MAIL DATE		DELIVERY MODE		
08/07/2008		PAPER		

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary

Application No.

10/806,242

Applicant(s)

MARKHOVSKY ET AL

Examiner

TEMICA M. BEAMER

Art Unit

2617

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --
Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 24 March 2004.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-121 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-121 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- 1) ☐ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-946)
- 3) ☐ Information Disclosure Statement(s) (PTO/SG/US)
Paper No(s)/Mail Date _____
- 4) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date _____
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: _____

DETAILED ACTION

Double Patenting

1. The nonstatutory double patenting rejection is based on a judicially created doctrine grounded in public policy (a policy reflected in the statute) so as to prevent the unjustified or improper timewise extension of the "right to exclude" granted by a patent and to prevent possible harassment by multiple assignees. A nonstatutory obviousness-type double patenting rejection is appropriate where the conflicting claims are not identical, but at least one examined application claim is not patentably distinct from the reference claim(s) because the examined application claim is either anticipated by, or would have been obvious over, the reference claim(s). See, e.g., *In re Berg*, 140 F.3d 1428, 46 USPQ2d 1226 (Fed. Cir. 1998); *In re Goodman*, 11 F.3d 1046, 29 USPQ2d 2010 (Fed. Cir. 1993); *In re Longi*, 759 F.2d 887, 225 USPQ 645 (Fed. Cir. 1985); *In re Van Ornum*, 686 F.2d 937, 214 USPQ 761 (CCPA 1982); *In re Vogel*, 422 F.2d 438, 164 USPQ 619 (CCPA 1970); and *In re Thorington*, 418 F.2d 528, 163 USPQ 644 (CCPA 1969).

A timely filed terminal disclaimer in compliance with 37 CFR 1.321(c) or 1.321(d) may be used to overcome an actual or provisional rejection based on a nonstatutory double patenting ground provided the conflicting application or patent either is shown to be commonly owned with this application, or claims an invention made as a result of activities undertaken within the scope of a joint research agreement.

Art Unit: 2617

Effective January 1, 1994, a registered attorney or agent of record may sign a terminal disclaimer. A terminal disclaimer signed by the assignee must fully comply with 37 CFR 3.73(b).

Claims 1-121 are provisionally rejected on the ground of nonstatutory obviousness-type double patenting as being unpatentable over claims 1-121 of copending Application No. 10/786,144. Although the conflicting claims are not identical, they are not patentably distinct from each other because the claims of the instant application are broadly encompassed by the claims of the application.

2. This is a provisional obviousness-type double patenting rejection because the conflicting claims have not in fact been patented.

Co-Pending Application

Instant Application

1. A system for finding a target, comprising: a transponder disposed on the target; a transceiver for monitoring the location of the target; a wireless communication system configured to allow communication between said transponder and said transceiver, and a processor configured to find the target by virtual triangulation <u>that does not use a fixed infrastructure</u> based on values of position information from said transponder and said transceiver.	1. A system for finding a target, comprising: a transponder disposed on the target; a transceiver for monitoring the location of the target; a wireless communication system configured to allow communication between said transponder and said transceiver, and a processor configured to find the target by virtual triangulation based on values of position information from said transponder and said transceiver.
2. The system for finding of claim 1, wherein said processor being configured to determine virtual triangulation based on successive values of said position information using at least three points P.sub.1, P.sub.2 and P.sub.3 of said transponder respective of said transceiver.	2. The system for finding of claim 1, wherein said processor being configured to determine virtual triangulation based on successive values of said position information using at least three points P1, P2 and P3 of said transponder respective of said transceiver.
3. The system for finding of claim 1, wherein said processor being configured to determine virtual triangulation based on successive values of said position information of said transponder respective of said transceiver using a means for successive pattern movement technique configured to find the target, whereby said means for successive pattern movement obtains and corrects the direction to the location of the target T based on said values of said position information.	3. The system for finding of claim 1, wherein said processor being configured to determine virtual triangulation based on successive values of said position information of said transponder respective of said transceiver using a means for successive pattern movement technique configured to find the target, whereby said means for successive pattern movement obtains and corrects the direction to the location of the target T based on said values of said position information.

Art Unit: 2617

4. The system for finding of claim 1, wherein said processor being configured to determine virtual triangulation based on successive values of said position information relating to the average speed of the motion of the user of said transponder respective of said transceiver.	4. The system for finding of claim 1, wherein said processor being configured to determine virtual triangulation based on successive values of said position information relating to the average speed of the motion of the user of said transponder respective of said transceiver.
5. The system for finding of claim 1, wherein said processor being configured to determine virtual triangulation based on successive values of said position information relating to input of a user of said transceiver, whereby said user input signals motion between said transponder respective of said transceiver begins.	5. The system for finding of claim 1, wherein said processor being configured to determine virtual triangulation based on successive values of said position information relating to input of a user of said transceiver, whereby said user input signals motion between said transponder respective of said transceiver begins.
6. The system for finding of claim 1, wherein said processor being configured to determine virtual triangulation based on successive values of the elapsed time a ranging signal transmitted by said transceiver to said transponder, said transponder transmitting a reply ranging signal to said transceiver, whereby said transceiver transmitting said ranging signal and receiving said reply ranging signals from said transponder a predetermined number of times sufficient to determine an elapsed time.	6. The system for finding of claim 1, wherein said processor being configured to determine virtual triangulation based on successive values of the elapsed time a ranging signal transmitted by said transceiver to said transponder, said transponder transmitting a reply ranging signal to said transceiver, whereby said transceiver transmitting said ranging signal and receiving said reply ranging signals from said transponder a predetermined number of times sufficient to determine an elapsed time.
7. The system for finding of claim 1, wherein said processor being configured to accumulate a phase shift between said ranging signal and said reply ranging signal.	7. The system for finding of claim 1, wherein said processor being configured to accumulate a phase shift between said ranging signal and said reply ranging signal.
8. The system for finding of claim 1, wherein said processor being configured with a phase shift detector.	8. The system for finding of claim 1, wherein said processor being configured with a phase shift detector.
9. The system for finding of claim 8, wherein said processor being configured to determine a value of an optimal operating resolution of said phase shift detector.	9. The system for finding of claim 8, wherein said processor being configured to determine a value of an optimal operating resolution of said phase shift detector.
10. The system for finding of claim 8, wherein said phase shift detector is configured to measure a value of said phase shift between said ranging signal and said reply ranging signal.	10. The system for finding of claim 8, wherein said phase shift detector is configured to measure a value of said phase shift between said ranging signal and said reply ranging signal.
11. The system for finding of claim 8, wherein said processor being configured to determine a value of said phase shift based on a value of a transmission interval.	11. The system for finding of claim 8, wherein said processor being configured to determine a value of said phase shift based on a value of a transmission interval.
12. The system for finding of claim 8, wherein said processor being configured to determine a value of said phase shift based on a value of a calibration interval.	12. The system for finding of claim 8, wherein said processor being configured to determine a value of said phase shift based on a value of a calibration interval.
13. The system for finding of claim 12, wherein said value of said calibration interval is periodically determined by each of said transponder and or said transceiver.	13. The system for finding of claim 12, wherein said value of said calibration interval is periodically determined by each of said transponder and or said transceiver.
14. The system for finding of claim 8, wherein said processor determines said phase shift based on a value	14. The system for finding of claim 8, wherein said processor determines said phase shift based on a value

Art Unit: 2617

<p>of an antenna propagation interval.</p> <p>15. The system according to claim 1, wherein said transceiver is configured to enter a homing mode for searching for the target, said homing mode being entered when a value of said position information between said transceiver and the target corresponds to a predetermined value.</p> <p>16. The system according to claim 15, wherein said homing mode toggled between states of on and off by a value of said position information of the target being equal to a predetermined value of a position ambiguity of the target.</p> <p>17. The system according to claim 16, wherein said transceiver is configured to exit said homing mode after an elapsed predetermined time period.</p> <p>18. The system according to claim 16, wherein said transceiver is configured to enter said homing mode to determine a location of the target when requested by input from a user.</p> <p>19. The system according to claim 1, wherein said processor is configured to reduce position ambiguity of transceiver respective of the target based on generating a value for input information signals on at least one band.</p> <p>20. The system according to claim 19, wherein said transceiver is configured to generate auditory signals representative of when said position ambiguity of the target is equal to a predetermined value for said position ambiguity.</p> <p>21. The system according to claim 1, wherein said processor is configured to operate on a band using on a spread spectrum to establish position information signals from said transponder and said transceiver.</p> <p>22. The system according to claim 1, wherein said transceiver being configured with an interface with the user so as to communicate to the user through said interface by one or more of the sensing group of audible, visual or physical.</p> <p>23. The system according to claim 22, wherein said interface includes a display for visually displaying said position information to the user.</p> <p>24. The system according to claim 23, wherein said display includes is LCD screen having means for indicating said position information to the user.</p> <p>25. The system according to claim 22, wherein said interface includes indicator means configured to display said position information to the user on a predetermined pattern.</p>	<p>of an antenna propagation interval.</p> <p>15. The system according to claim 1, wherein said transceiver is configured to enter a homing mode for searching for the target, said homing mode being entered when a value of said position information between said transceiver and the target corresponds to a predetermined value.</p> <p>16. The system according to claim 15, wherein said homing mode toggled between states of on and off by a value of said position information of the target being equal to a predetermined value of a position ambiguity of the target.</p> <p>17. The system according to claim 16, wherein said transceiver is configured to exit said homing mode after an elapsed predetermined time period.</p> <p>18. The system according to claim 16, wherein said transceiver is configured to enter said homing mode to determine a location of the target when requested by input from a user.</p> <p>19. The system according to claim 1, wherein said processor is configured to reduce position ambiguity of transceiver respective of the target based on generating a value for input information signals on at least one band.</p> <p>20. The system according to claim 19, wherein said transceiver is configured to generate auditory signals representative of when said position ambiguity of the target is equal to a predetermined value for said position ambiguity.</p> <p>21. The system according to claim 1, wherein said processor is configured to operate on a band using on a spread spectrum to establish position information signals from said transponder and said transceiver.</p> <p>22. The system according to claim 1, wherein said transceiver being configured with an interface with the user so as to communicate to the user through said interface by one or more of the sensing group of audible, visual or physical.</p> <p>23. The system according to claim 22, wherein said interface includes a display for visually displaying said position information to the user.</p> <p>24. The system according to claim 23, wherein said display includes is LCD screen having means for indicating said position information to the user.</p> <p>25. The system according to claim 22, wherein said interface includes indicator means configured to display said position information to the user on a predetermined pattern.</p>
---	---

Art Unit: 2617

<p>26. The system according to claim 2, wherein said values from said three points P.sub.1, P.sub.2 and P.sub.3 create a point of intersection of circles based on circles with radii R.sub.1, R.sub.2 and R.sub.3 originating from said points P.sub.1, P.sub.2 and P.sub.3, respectively, whereby said point of intersection finds the target respective of said transceiver.</p>	<p>26. The system according to claim 2, wherein said values from said three points P.sub.1, P.sub.2 and P.sub.3 create a point of intersection of circles based on circles with radii R.sub.1, R.sub.2 and R.sub.3 originating from said points P.sub.1, P.sub.2 and P.sub.3, respectively, whereby said point of intersection finds the target respective of said transceiver.</p>
<p>27. The system according to claim 1, wherein said transceiver is configured to adjust adaptively a power value of a transmitter of said transceiver so as to improve a value of said position information.</p>	<p>27. The system according to claim 1, wherein said transceiver is configured to adjust adaptively a power value of a transmitter of said transceiver so as to improve a value of said position information.</p>
<p>28. The system according to claim 1, wherein said transceiver is configured to adjust adaptively a sensitivity value of a receiver of said transceiver so as to improve a value of said position information.</p>	<p>28. The system according to claim 1, wherein said transceiver is configured to adjust adaptively a sensitivity value of a receiver of said transceiver so as to improve a value of said position information.</p>
<p>29. The system according to claim 1, wherein said transponder is configured to adjust adaptively a power value of a transmitter of said transponder so as to improve a value of said position information.</p>	<p>29. The system according to claim 1, wherein said transponder is configured to adjust adaptively a power value of a transmitter of said transponder so as to improve a value of said position information.</p>
<p>30. The system according to claim 1, wherein said transponder is configured to adjust adaptively a sensitivity value of a receiver of said transponder so as to improve a value of said position information.</p>	<p>30. The system according to claim 1, wherein said transponder is configured to adjust adaptively a sensitivity value of a receiver of said transponder so as to improve a value of said position information.</p>
<p>31. The system according to claim 1, wherein said processor being configured to be in communication with an antenna, said processor being configured to repeatedly determine values for said position information based on one or more of the following values for: a transmission interval between said transceiver and said transponder, said transmission interval being an elapsed time between transmitting said ranging signal and receiving said reply ranging signal, a calibration interval between each of said transceiver and transponder said calibration interval being a time interval of a period to normalize the circuitry of said transponder and said transceiver, and an antenna propagation interval of either of said transceiver or said transponder, or both, said antenna propagation interval being an elapsed time of a signal measured as it passes through said antenna of said transponder or said transceiver.</p>	<p>31. The system according to claim 1, wherein said processor being configured to be in communication with an antenna, said processor being configured to repeatedly determine values for said position information based on one or more of the following values for: a transmission interval between said transceiver and said transponder, said transmission interval being an elapsed time between transmitting said ranging signal and receiving said reply ranging signal, a calibration interval between each of said transceiver and transponder said calibration interval being a time interval of a period to normalize the circuitry of said transponder and said transceiver, and an antenna propagation interval of either of said transceiver or said transponder, or both, said antenna propagation interval being an elapsed time of a signal measured as it passes through said antenna of said transponder or said transceiver.</p>
<p>32. The system according to claim 1, wherein said processor is configured for communication with an antenna to repeatedly determine values for said position information based on a value for a measured distance between said transponder and said transceiver.</p>	<p>32. The system according to claim 1, wherein said processor is configured for communication with an antenna to repeatedly determine values for said position information based on a value for a measured distance between said transponder and said transceiver.</p>
<p>33. The system according to claim 1, wherein said transceiver is configured for transmitting a ranging signal to said transponder, said transponder is configured for responding to said ranging signal by transmitting a reply ranging signal to said transceiver, and said processor is configured to determine a value of a measured distance</p>	<p>33. The system according to claim 1, wherein said transceiver is configured for transmitting a ranging signal to said transponder, said transponder is configured for responding to said ranging signal by transmitting a reply ranging signal to said transceiver, and said processor is configured to determine a value of a measured distance</p>

Art Unit: 2617

<p>between said transponder and said transceiver based on position information from said ranging signal and said reply ranging signal.</p> <p>34. A method, comprises the steps of: determining a value of a point P.sub.1 from position information received by a transceiver corresponding to a location of a transponder disposed on a target; prompting said user to move said transceiver to a point P.sub.2 relative to a location of the target; determining a value of a point P.sub.2 from position information received by said transceiver corresponding to a location of said transponder; prompting said user to move said transceiver to a point P.sub.3 relative to a location of the target; determining a value of a point P.sub.3 from position information received by said transceiver corresponding to a location of said transponder; and finding the location of the target by virtual triangulation in accordance with each of said values for said points P.sub.1, P.sub.2 and P.sub.3 of position information received by said transceiver.</p> <p>35. The method of claim 34 wherein said step of determining said position information further comprises repeating as necessary the steps of: prompting a user to move said transceiver to a point P.sub.n relative to a location of said target having said transponder; determining a value of a point P.sub.n from position information received by said transceiver corresponding to a location of said transponder; and finding the location of the target from position information received by said transceiver by repeating said determining by virtual triangulation for two of each of said values for said points P.sub.1, P.sub.2 or P.sub.3 and said point P.sub.n.</p> <p>36. The method of claim 34 wherein said step of determining said position information further comprises the steps of: determining said values of said position information of said target by: determining a transmission interval between said transceiver and said transponder; determining a calibration interval between each of said transceiver and transponder; and determining an antenna propagation interval of each of said transceiver and transponder.</p> <p>37. The method of claim 36 wherein said step of determining said position information further comprises the steps of: determining said transmission interval based on an elapsed time between transmitting said ranging signal and receiving said reply ranging signal.</p> <p>38. The method of claim 36 wherein said step of determining said position information further comprises the steps of: determining said calibration interval based on a time interval of a period to normalize the circuitry of said transceiver and said transponder.</p> <p>39. The method of claim 36 wherein said step of determining said position information further comprises</p>	<p>between said transponder and said transceiver based on position information from said ranging signal and said reply ranging signal.</p> <p>34. A method, comprises the steps of: determining a value of a point P.sub.1 from position information received by a transceiver corresponding to a location of a transponder disposed on a target; prompting said user to move said transceiver to a point P.sub.2 relative to a location of the target; determining a value of a point P.sub.2 from position information received by said transceiver corresponding to a location of said transponder; prompting said user to move said transceiver to a point P.sub.3 relative to a location of the target; determining a value of a point P.sub.3 from position information received by said transceiver corresponding to a location of said transponder; and finding the location of the target by virtual triangulation in accordance with each of said values for said points P.sub.1, P.sub.2 and P.sub.3 of position information received by said transceiver.</p> <p>35. The method of claim 34 wherein said step of determining said position information further comprises repeating as necessary the steps of: prompting a user to move said transceiver to a point P.sub.n relative to a location of said target having said transponder; determining a value of a point P.sub.n from position information received by said transceiver corresponding to a location of said transponder; and finding the location of the target from position information received by said transceiver by repeating said determining by virtual triangulation for two of each of said values for said points P.sub.1, P.sub.2 or P.sub.3 and said point P.sub.n.</p> <p>36. The method of claim 34 wherein said step of determining said position information further comprises the steps of: determining said values of said position information of said target by: determining a transmission interval between said transceiver and said transponder; determining a calibration interval between each of said transceiver and transponder; and determining an antenna propagation interval of each of said transceiver and transponder.</p> <p>37. The method of claim 36 wherein said step of determining said position information further comprises the steps of: determining said transmission interval based on an elapsed time between transmitting said ranging signal and receiving said reply ranging signal.</p> <p>38. The method of claim 36 wherein said step of determining said position information further comprises the steps of: determining said calibration interval based on a time interval of a period to normalize the circuitry of said transceiver and said transponder.</p> <p>39. The method of claim 36 wherein said step of determining said position information further comprises</p>
---	---

Art Unit: 2617

<p>the steps of: determining said antenna propagation interval based on an elapsed time of a signal measured passing through said antenna of said transceiver and said transponder.</p> <p>40. The method of claim 36 wherein said step of determining said position information further comprises the steps of: generating a measured distance between each of said transceiver and said transponder.</p>	<p>the steps of: determining said antenna propagation interval based on an elapsed time of a signal measured passing through said antenna of said transceiver and said transponder.</p> <p>40. The method of claim 36 wherein said step of determining said position information further comprises the steps of: generating a measured distance between each of said transceiver and said transponder.</p>
<p>41. The method of claim 40 wherein said step of determining said position information further comprises the steps of: determining said position information of the target generated by a virtual triangulation relationship when successive values of said position information have a predetermined logical relationship relative to said previous values between said transceiver and said transponder.</p>	<p>41. The method of claim 40 wherein said step of determining said position information further comprises the steps of: determining said position information of the target generated by a virtual triangulation relationship when successive values of said position information have a predetermined logical relationship relative to said previous values between said transceiver and said transponder.</p>
<p>42. The method of claim 36 wherein said step of determining said position information further comprises the steps of: generating a measured distance between each of said transceiver and said transponder.</p>	<p>42. The method of claim 36 wherein said step of determining said position information further comprises the steps of: generating a measured distance between each of said transceiver and said transponder.</p>
<p>43. A computer-readable medium having stored thereon a plurality of sequences of instructions, said plurality of sequences of instructions including sequences of instructions which, when executed by a processor, cause said processor to perform the steps of: determining a value of a point P.sub.1 from position information received by a transceiver corresponding to a location of a transponder disposed on a target; prompting said user to move said transceiver to a point P.sub.2 relative to a location of the target; determining a value of a point P.sub.2 from position information received by said transceiver corresponding to a location of said transponder; prompting said user to move said transceiver to a point P.sub.3 relative to a location of the target; determining a value of a point P.sub.3 from position information received by said transceiver corresponding to a location of said transponder; and finding the location of the target in accordance with each of said values for said points P.sub.1, P.sub.2 and P.sub.3 of position information received by said transceiver.</p>	<p>43. A computer-readable medium having stored thereon a plurality of sequences of instructions, said plurality of sequences of instructions including sequences of instructions which, when executed by a processor, cause said processor to perform the steps of: determining a value of a point P.sub.1 from position information received by a transceiver corresponding to a location of a transponder disposed on a target; prompting said user to move said transceiver to a point P.sub.2 relative to a location of the target; determining a value of a point P.sub.2 from position information received by said transceiver corresponding to a location of said transponder; prompting said user to move said transceiver to a point P.sub.3 relative to a location of the target; determining a value of a point P.sub.3 from position information received by said transceiver corresponding to a location of said transponder; and finding the location of the target in accordance with each of said values for said points P.sub.1, P.sub.2 and P.sub.3 of position information received by said transceiver.</p>
<p>44. A computer-readable medium having stored thereon a plurality of sequences of instructions, said plurality of sequences of instructions including sequences of instructions which, when executed by a processor, cause said processor to perform the steps of: determining successive values of position information of a transceiver respective of a transponder disposed on a target; finding using virtual triangulation the location of the target T based on said values of said position information, and correcting position ambiguity of the location of the target based on said values of said position information.</p>	<p>44. A computer-readable medium having stored thereon a plurality of sequences of instructions, said plurality of sequences of instructions including sequences of instructions which, when executed by a processor, cause said processor to perform the steps of: determining successive values of position information of a transceiver respective of a transponder disposed on a target; finding using virtual triangulation the location of the target T based on said values of said position information, and correcting position ambiguity of the location of the target based on said values of said position information.</p>
<p>45. A computer-readable medium having stored thereon</p>	<p>45. A computer-readable medium having stored thereon</p>

Art Unit: 2617

<p>a plurality of sequences of instructions, said plurality of sequences of instructions including sequences of instructions which, when executed by a processor, cause said processor to perform the steps of: determining successive values of position information of a transceiver respective of a transponder disposed on a target; and finding using virtual triangulation the location of the target T based on said values of said position information based on successive values of said position information relating to the average speed of the motion of the user of said transponder respective of said transceiver.</p>	<p>a plurality of sequences of instructions, said plurality of sequences of instructions including sequences of instructions which, when executed by a processor, cause said processor to perform the steps of: determining successive values of position information of a transceiver respective of a transponder disposed on a target; and finding using virtual triangulation the location of the target T based on said values of said position information based on successive values of said position information relating to the average speed of the motion of the user of said transponder respective of said transceiver.</p>
<p>46. A computer-readable medium having stored thereon a plurality of sequences of instructions, said plurality of sequences of instructions including sequences of instructions which, when executed by a processor, cause said processor to perform the steps of: determining successive values of position information of a transceiver respective of a transponder disposed on a target; finding using virtual triangulation the location of the target T based on successive values of said position information relating to input of a user of said transceiver, whereby said user input signals motion between said transponder respective of said transceiver begins.</p>	<p>46. A computer-readable medium having stored thereon a plurality of sequences of instructions, said plurality of sequences of instructions including sequences of instructions which, when executed by a processor, cause said processor to perform the steps of: determining successive values of position information of a transceiver respective of a transponder disposed on a target; finding using virtual triangulation the location of the target T based on successive values of said position information relating to input of a user of said transceiver, whereby said user input signals motion between said transponder respective of said transceiver begins.</p>
<p>47. A portable device for tracking a target, comprising: processor for determining position information of the target; memory operably connected to said processor, wherein said memory being configured to store a plurality of sequences of instructions, said plurality of sequences of instructions including sequences of instructions which, when executed by said processor, cause said processor to perform the steps of: determining a value of a point P.sub.1 from position information received by a transceiver corresponding to a location of a transponder disposed on a target; prompting said user to move said transceiver to a point P.sub.2 relative to a location of the target; determining a value of a point P.sub.2 from position information received by said transceiver corresponding to a location of said transponder; prompting said user to move said transceiver to a point P.sub.3 relative to a location of the target; determining a value of a point P.sub.3 from position information received by said transceiver corresponding to a location of said transponder; and finding the location of the target by virtual triangulation in accordance with each of said values for said points P.sub.1, P.sub.2 and P.sub.3 of position information received by said transceiver.</p>	<p>47. A portable device for tracking a target, comprising: processor for determining position information of the target; memory operably connected to said processor, wherein said memory being configured to store a plurality of sequences of instructions, said plurality of sequences of instructions including sequences of instructions which, when executed by said processor, cause said processor to perform the steps of: determining a value of a point P.sub.1 from position information received by a transceiver corresponding to a location of a transponder disposed on a target; prompting said user to move said transceiver to a point P.sub.2 relative to a location of the target; determining a value of a point P.sub.2 from position information received by said transceiver corresponding to a location of said transponder; prompting said user to move said transceiver to a point P.sub.3 relative to a location of the target; determining a value of a point P.sub.3 from position information received by said transceiver corresponding to a location of said transponder; and finding the location of the target by virtual triangulation in accordance with each of said values for said points P.sub.1, P.sub.2 and P.sub.3 of position information received by said transceiver.</p>
<p>48. The portable device of claim 47 wherein said processor further repeating as necessary the steps of: prompting a user to move said transceiver to a point P.sub.n relative to a location of said target having said transponder; determining a value of a point P.sub.n from position information received by said transceiver corresponding to a location of said transponder; and finding the location of the target from position information received by said transceiver by repeating said determining by virtual triangulation for two of each of said</p>	<p>48. The portable device of claim 47 wherein said processor further repeating as necessary the steps of: prompting a user to move said transceiver to a point P.sub.n relative to a location of said target having said transponder; determining a value of a point P.sub.n from position information received by said transceiver corresponding to a location of said transponder; and finding the location of the target from position information received by said transceiver by repeating said determining by virtual triangulation for two of each of said</p>

Art Unit: 2617

<p>values for said points P.sub.1, P.sub.2 or P.sub.3 and said point P.sub.n.</p>	<p>values for said points P.sub.1, P.sub.2 or P.sub.3 and said point P.sub.n.</p>
<p>49. The portable device of claim 47 wherein said processor further executing the steps of: determining said values of said position information of said target by: determining a transmission interval between said transceiver and said transponder; determining a calibration interval between each of said transceiver and transponder; and determining an antenna propagation interval of each of said transceiver and transponder.</p>	<p>49. The portable device of claim 47 wherein said processor further executing the steps of: determining said values of said position information of said target by: determining a transmission interval between said transceiver and said transponder; determining a calibration interval between each of said transceiver and transponder; and determining an antenna propagation interval of each of said transceiver and transponder.</p>
<p>50. The portable device of claim 49 wherein said processor further executing the steps of: determining said transmission interval based on an elapsed time between transmitting said ranging signal and receiving said reply ranging signal.</p>	<p>50. The portable device of claim 49 wherein said processor further executing the steps of: determining said transmission interval based on an elapsed time between transmitting said ranging signal and receiving said reply ranging signal.</p>
<p>51. The portable device of claim 49 wherein said processor further executing the steps of: determining said calibration interval based on a time interval of a period to normalize the circuitry of said transceiver and said transponder.</p>	<p>51. The portable device of claim 49 wherein said processor further executing the steps of: determining said calibration interval based on a time interval of a period to normalize the circuitry of said transceiver and said transponder.</p>
<p>52. The portable device of claim 49 wherein said processor further executing the steps of: determining said antenna propagation interval based on an elapsed time of a signal measured passing through said antenna of said transceiver and said transponder.</p>	<p>52. The portable device of claim 49 wherein said processor further executing the steps of: determining said antenna propagation interval based on an elapsed time of a signal measured passing through said antenna of said transceiver and said transponder.</p>
<p>53. The portable device of claim 49 wherein said processor further executing the steps of: generating a measured distance between each of said transceiver and said transponder.</p>	<p>53. The portable device of claim 49 wherein said processor further executing the steps of: generating a measured distance between each of said transceiver and said transponder.</p>
<p>54. The portable device of claim 53 wherein said processor further executing the steps of: determining said position information of the target generated by a Virtual triangulation relationship when successive values of said position information have a predetermined logical relationship relative to said previous values between said transceiver and said transponder.</p>	<p>54. The portable device of claim 53 wherein said processor further executing the steps of: determining said position information of the target generated by a virtual triangulation relationship when successive values of said position information have a predetermined logical relationship relative to said previous values between said transceiver and said transponder.</p>
<p>55. A mobile system for tracking a target T, comprising: a unit disposed on the target T; a monitoring unit for monitoring the location of the target T; a wireless communication system operating on at least one Radio Frequency (RF) band, said wireless communication system being configured to allow communication between configured to allow communication between at least two monitoring units and the target T, and a processor configured to find the target T by virtual triangulation based on values of position information from said monitoring unit and said unit disposed on the target T.</p>	<p>55. A mobile system for tracking a target T, comprising: a unit disposed on the target T; a monitoring unit for monitoring the location of the target T; a wireless communication system operating on at least one Radio Frequency (RF) band, said wireless communication system being configured to allow communication between configured to allow communication between at least two monitoring units and the target T, and a processor configured to find the target T by virtual triangulation based on values of position information from said monitoring unit and said unit disposed on the target T.</p>
<p>56. The mobile system according to claim 55, wherein said processor being configured to be in communication with an antenna, said processor being configured to</p>	<p>56. The mobile system according to claim 55, wherein said processor being configured to be in communication with an antenna, said processor being configured to</p>

Art Unit: 2617

<p>repeatedly determine values for said position information from: a transmission interval between said monitoring unit and the target T, a calibration interval between each of said monitoring unit and the target T, and an antenna propagation interval of said monitoring unit and the target T.</p> <p>57. The mobile system according to claim 56, wherein further comprising: means for generating values of a measured distance between units, said generating means determining said values of said measured distance between said monitoring unit and the target T based on a virtual triangulation relationship using said position information.</p>	<p>repeatedly determine values for said position information from: a transmission interval between said monitoring unit and the target T, a calibration interval between each of said monitoring unit and the target T, and an antenna propagation interval of said monitoring unit and the target T.</p> <p>57. The mobile system according to claim 56, wherein further comprising: means for generating values of a measured distance between units, said generating means determining said values of said measured distance between said monitoring unit and the target T based on a virtual triangulation relationship using said position information.</p>
<p>58. The mobile system according to claim 57, wherein said processor being configured to be in communication with an antenna, said processor being configured to repeatedly determine values for said position information from: a transmission interval between said monitoring unit and the target T, a calibration interval between each of said monitoring unit and the target T, and an antenna propagation interval of said monitoring unit and the target T.</p> <p>59. The mobile system according to claim 56, wherein said transmission interval being an elapsed time between transmitting said ranging signal and receiving said reply ranging signal.</p> <p>60. The mobile system according to claim 56, wherein said calibration interval being a time interval of a period to normalize the circuitry of said monitoring unit and the target T.</p> <p>61. The mobile system according to claim 56, wherein said antenna propagation interval being an elapsed time of a signal measured as it passes through said antenna of said monitoring unit and the target T.</p> <p>62. The mobile system according to claim 56, wherein said system being configured to generate said virtual triangulation from said position information from a plurality of monitoring units or units disposed on the target T.</p> <p>63. The mobile system according to claim 56, further comprising a plurality of monitoring units being configured to generate said virtual triangulation from said position information based on values received from said monitoring unit, or said units disposed on the target T, or units adjacent the target T.</p> <p>64. The mobile system according to claim 63, whereby said monitoring unit or said units disposed on the target T or units adjacent the target T, are linked dynamically so as to form a mobile network adapted to locate, track and determine the position of each of said plurality of units.</p>	<p>58. The mobile system according to claim 57, wherein said processor being configured to be in communication with an antenna, said processor being configured to repeatedly determine values for said position information from: a transmission interval between said monitoring unit and the target T, a calibration interval between each of said monitoring unit and the target T, and an antenna propagation interval of said monitoring unit and the target T.</p> <p>59. The mobile system according to claim 56, wherein said transmission interval being an elapsed time between transmitting said ranging signal and receiving said reply ranging signal.</p> <p>60. The mobile system according to claim 56, wherein said calibration interval being a time interval of a period to normalize the circuitry of said monitoring unit and the target T.</p> <p>61. The mobile system according to claim 56, wherein said antenna propagation interval being an elapsed time of a signal measured as it passes through said antenna of said monitoring unit and the target T.</p> <p>62. The mobile system according to claim 56, wherein said system being configured to generate said virtual triangulation from said position information from a plurality of monitoring units or units disposed on the target T.</p> <p>63. The mobile system according to claim 56, further comprising a plurality of monitoring units being configured to generate said virtual triangulation from said position information based on values received from said monitoring unit, or said units disposed on the target T, or units adjacent the target T.</p> <p>64. The mobile system according to claim 63, whereby said monitoring unit or said units disposed on the target T or units adjacent the target T, are linked dynamically so as to form a mobile network adapted to locate, track and determine the position of each of said plurality of units.</p>

Art Unit: 2617

<p>65. The mobile system according to claim 64, wherein said mobile network being configured to enable a coordinated search to intercept the target T.</p>	<p>65. The mobile system according to claim 64, wherein said mobile network being configured to enable a coordinated search to intercept the target T.</p>
<p>66. The mobile system according to claim 65, wherein said monitoring unit of said mobile network configured having an indicator means adapted to illustrate to each of said monitoring units in a predetermined range, said indicator means configured to instruct respective monitoring units to move coordinately so as to converge on said target T based on said position information determined by said virtual triangulation relationship.</p>	<p>66. The mobile system according to claim 65, wherein said monitoring unit of said mobile network configured having an indicator means adapted to illustrate to each of said monitoring units in a predetermined range, said indicator means configured to instruct respective monitoring units to move coordinately so as to converge on said target T based on said position information determined by said virtual triangulation relationship.</p>
<p>67. The mobile system according to claim 56, wherein said position information determines values for three points P.sub.1, P.sub.2 and P.sub.3 so as to create a point of intersection of circles with radii R.sub.1, R.sub.2 and R.sub.3 originating from said points P.sub.1, P.sub.2 and P.sub.3, respectively, whereby said point of intersection finds the target respective of each of said monitoring units.</p>	<p>67. The mobile system according to claim 56, wherein said position information determines values for three points P.sub.1, P.sub.2 and P.sub.3 so as to create a point of intersection of circles with radii R.sub.1, R.sub.2 and R.sub.3 originating from said points P.sub.1, P.sub.2 and P.sub.3, respectively, whereby said point of intersection finds the target respective of each of said monitoring units.</p>
<p>68. The mobile system according to claim 56, wherein said processor being configured to determine virtual triangulation based on successive values of said position information using at least three points P.sub.1, P.sub.2 and P.sub.3 of said monitoring unit respective of said unit disposed on the target T.</p>	<p>68. The mobile system according to claim 56, wherein said processor being configured to determine virtual triangulation based on successive values of said position information using at least three points P.sub.1, P.sub.2 and P.sub.3 of said monitoring unit respective of said unit disposed on the target T.</p>
<p>69. The mobile system according to claim 56, wherein said processor being configured to determine virtual triangulation based on successive values of said position information of said transponder respective of said transceiver using a means for position ambiguity reduction (PAR) configured to find the target, whereby said PAR means obtains and corrects the direction to the location of the target T based on said values of said position information.</p>	<p>69. The mobile system according to claim 56, wherein said processor being configured to determine virtual triangulation based on successive values of said position information of said transponder respective of said transceiver using a means for position ambiguity reduction (PAR) configured to find the target, whereby said PAR means obtains and corrects the direction to the location of the target T based on said values of said position information.</p>
<p>70. The mobile system according to claim 56, wherein said processor being configured to determine virtual triangulation based on successive values of said position information relating to the average speed of the motion of the user of said unit slave unit respective of said master unit.</p>	<p>70. The mobile system according to claim 56, wherein said processor being configured to determine virtual triangulation based on successive values of said position information relating to the average speed of the motion of the user of said unit slave unit respective of said master unit.</p>
<p>71. The mobile system according to claim 56, wherein said processor being configured to determine virtual triangulation based on successive values of said position information relating to input of a user of said transceiver, whereby said user input signals motion based on slave unit respective of said master unit begins.</p>	<p>71. The mobile system according to claim 56, wherein said processor being configured to determine virtual triangulation based on successive values of said position information relating to input of a user of said transceiver, whereby said user input signals motion based on slave unit respective of said master unit begins.</p>
<p>72. The mobile system according to claim 56, wherein said processor is configured to operate on a band using on a spread spectrum to establish position information signals from said slave unit respective of said master unit.</p>	<p>72. The mobile system according to claim 56, wherein said processor is configured to operate on a band using on a spread spectrum to establish position information signals from said slave unit respective of said master unit.</p>

Art Unit: 2617

<p>73. A computer-readable medium having stored thereon a plurality of sequences of instructions, said plurality of sequences of instructions including sequences of instructions which, when executed by a processor, cause said processor to perform the steps of: determining a value of a point P.sub.1 from position information received by a transceiver corresponding to a location of a transponder disposed on a target; prompting said user of a predetermined transceiver to move said predetermined transceiver to a point P.sub.2 relative to a location of the target; determining a value of a point P.sub.2 from position information of said predetermined transceiver corresponding to a location of said transponder; requesting said value of said point P.sub.2 of said predetermined transceiver; requesting a value of a point P.sub.3 corresponding to a location of said predetermined transceiver; and finding the location of the target in accordance with each of said values for said points P.sub.1, P.sub.2 and P.sub.3.</p>	<p>73. A computer-readable medium having stored thereon a plurality of sequences of instructions, said plurality of sequences of instructions including sequences of instructions which, when executed by a processor, cause said processor to perform the steps of: determining a value of a point P.sub.1 from position information received by a transceiver corresponding to a location of a transponder disposed on a target; prompting said user of a predetermined transceiver to move said predetermined transceiver to a point P.sub.2 relative to a location of the target; determining a value of a point P.sub.2 from position information of said predetermined transceiver corresponding to a location of said transponder; requesting said value of said point P.sub.2 of said predetermined transceiver; requesting a value of a point P.sub.3 corresponding to a location of said predetermined transceiver; and finding the location of the target in accordance with each of said values for said points P.sub.1, P.sub.2 and P.sub.3.</p>
<p>74. A system for finding a target, comprising: a tracked unit, said tracked unit being configured with a transponder and is disposed on the target; a monitoring unit, said monitoring unit being configured with a transceiver, said monitoring unit configured for monitoring and tracking the location of the target; a communication system configured to communicate between said transponder and said transceiver on radio frequency band, and whereby said monitoring device has means for generating a measured distance between said monitoring device and said tracked unit, said monitoring device has means for determining the monitoring and tracking of the location of the target by a virtual triangulation relationship without need for additional points of references.</p>	<p>74. A system for finding a target, comprising: a tracked unit, said tracked unit being configured with a transponder and is disposed on the target; a monitoring unit, said monitoring unit being configured with a transceiver, said monitoring unit configured for monitoring and tracking the location of the target; a communication system configured to communicate between said transponder and said transceiver on radio frequency band, and whereby said monitoring device has means for generating a measured distance between said monitoring device and said tracked unit, said monitoring device has means for determining the monitoring and tracking of the location of the target by a virtual triangulation relationship without need for additional points of references.</p>
<p>75. The system for finding the target of claim 74, wherein said monitoring unit moves in a virtual triangulation pattern where successive movements of said monitoring unit are based on logical, algorithmic and mathematical relationships between said measured distance values between said monitoring unit and said tracked unit.</p>	<p>75. The system for finding the target of claim 74, wherein said monitoring unit moves in a virtual triangulation pattern where successive movements of said monitoring unit are based on logical, algorithmic and mathematical relationships between said measured distance values between said monitoring unit and said tracked unit.</p>
<p>76. The system for finding the target of claim 74, wherein said monitoring unit includes means for generating a measured distance between locations of successive movements of said monitoring unit or between successive locations of said monitoring unit as input by the user.</p>	<p>76. The system for finding the target of claim 74, wherein said monitoring unit includes means for generating a measured distance between locations of successive movements of said monitoring unit or between successive locations of said monitoring unit as input by the user.</p>
<p>77. The system for finding the target of claim 76, wherein said monitoring unit moves in a virtual triangulation pattern where successive movements of said monitoring unit are based on logical, algorithmic and mathematical relationships between said measured distance values between said monitoring unit and said tracked unit, and said distance values between said monitoring unit</p>	<p>77. The system for finding the target of claim 76, wherein said monitoring unit moves in a virtual triangulation pattern where successive movements of said monitoring unit are based on logical, algorithmic and mathematical relationships between said measured distance values between said monitoring unit and said tracked unit, and said distance values between said monitoring unit</p>

Art Unit: 2617

<p>successive locations.</p> <p>78. The system for finding the target of claim 77, wherein said monitoring unit generates visual and audio information prompts for said monitoring unit successive movement.</p> <p>79. The system for finding the target of claim 78, wherein said monitoring unit generates visual and audio information that conveys said monitoring unit successive movements and said target movements, and said monitoring unit and said target relative location as well the bearing angle to the target.</p> <p>80. The system for finding the target of claim 79, wherein said monitoring or tracked units are configured with GPS, compass or other position and/or direction determining devices.</p> <p>81. The system for finding the target of claim 80, wherein said monitoring unit generates visual and audio information that conveys said monitoring unit and the target successive movements, relative location and or absolute location.</p> <p>82. The system for finding the target of claim 80, wherein said monitoring unit generates visual and audio information that conveys said monitoring unit and the target successive movements, relative location and or absolute location.</p> <p>83. The system for finding the target of claim 74, wherein any three said monitoring units are stationary and are not located on the same straight line.</p> <p>84. The system for finding the target of claim 83, wherein said three stationary monitoring units can form a virtual system of coordinates in which the coordinates of the said three stationary monitoring units and the coordinates can be determined of all of the mobile monitoring units and targets that are within the communication range of said three stationary monitoring units.</p> <p>85. The system for finding the target of claim 84, wherein said mobile monitoring unit generates visual and audio information prompts for said monitoring unit successive movement.</p> <p>86. The system for finding the target of claim 85, wherein said mobile monitoring unit generates visual and audio information that conveys said virtual scaled coordinates together with said mobile monitoring unit and the target relative location, and successive movements of said mobile monitoring unit and said target, and said bearing angle from said mobile monitoring unit to the target, and said stationary monitoring units relative location.</p> <p>87. The system for finding the target of claim 86, wherein</p>	<p>successive locations.</p> <p>78. The system for finding the target of claim 77, wherein said monitoring unit generates visual and audio information prompts for said monitoring unit successive movement.</p> <p>79. The system for finding the target of claim 78, wherein said monitoring unit generates visual and audio information that conveys said monitoring unit successive movements and said target movements, and said monitoring unit and said target relative location as well the bearing angle to the target.</p> <p>80. The system for finding the target of claim 79, wherein said monitoring or tracked units are configured with GPS, compass or other position and/or direction determining devices.</p> <p>81. The system for finding the target of claim 80, wherein said monitoring unit generates visual and audio information that conveys said monitoring unit and the target successive movements, relative location and or absolute location.</p> <p>82. The system for finding the target of claim 80, wherein said monitoring unit generates visual and audio information that conveys said monitoring unit and the target successive movements, relative location and or absolute location.</p> <p>83. The system for finding the target of claim 74, wherein any three said monitoring units are stationary and are not located on the same straight line.</p> <p>84. The system for finding the target of claim 83, wherein said three stationary monitoring units can form a virtual system of coordinates in which the coordinates of the said three stationary monitoring units and the coordinates can be determined of all of the mobile monitoring units and targets that are within the communication range of said three stationary monitoring units.</p> <p>85. The system for finding the target of claim 84, wherein said mobile monitoring unit generates visual and audio information prompts for said monitoring unit successive movement.</p> <p>86. The system for finding the target of claim 85, wherein said mobile monitoring unit generates visual and audio information that conveys said virtual scaled coordinates together with said mobile monitoring unit and the target relative location, and successive movements of said mobile monitoring unit and said target, and said bearing angle from said mobile monitoring unit to the target, and said stationary monitoring units relative location.</p> <p>87. The system for finding the target of claim 86, wherein</p>
---	---

Art Unit: 2617

<p>the data processing is performed by any said monitoring unit, stationary or mobile, or in a distributed fashion.</p>	<p>the data processing is performed by any said monitoring unit, stationary or mobile, or in a distributed fashion.</p>
<p>88. The system for finding the target of claim 87, wherein said monitoring and tracked units are combined with GPS, compass or other position and/or direction determining devices.</p>	<p>88. The system for finding the target of claim 87, wherein said monitoring and tracked units are combined with GPS, compass or other position and/or direction determining devices.</p>
<p>89. The system for finding the target of claim 88, wherein each mobile or stationary monitoring unit is equipped with a compass.</p>	<p>89. The system for finding the target of claim 88, wherein each mobile or stationary monitoring unit is equipped with a compass.</p>
<p>90. The system for finding the target of claim 74 whereby an ambiguity zone is decreased by increasing a distance between each of points P.sub.1, P.sub.2 and P.sub.3, said distance is increased between two of said points P.sub.1, P.sub.2 or P.sub.3 from an approximate value of 1.75°E to 4°E to reduce said ambiguity zone formed between each of said tracked units, whereby E is a maximum error in said distance measured between two of said points P.sub.1, P.sub.2 or P.sub.3, a width of said ambiguity zone is equal to E, and a length of said ambiguity zone is less than 2°E.</p>	<p>90. The system for finding the target of claim 74 whereby an ambiguity zone is decreased by increasing a distance between each of points P.sub.1, P.sub.2 and P.sub.3, said distance is increased between two of said points P.sub.1, P.sub.2 or P.sub.3 from an approximate value of 1.75°E to 4°E to reduce said ambiguity zone formed between each of said tracked units, whereby E is a maximum error in said distance measured between two of said points P.sub.1, P.sub.2 or P.sub.3, a width of said ambiguity zone is equal to E, and a length of said ambiguity zone is less than 2°E.</p>
<p>91. The system for finding the target of claim 74, whereby an ambiguity zone is reduced by increasing a distance between each of points P.sub.1, P.sub.2 and P.sub.3, said distance is increased between two of said points P.sub.1, P.sub.2 or P.sub.3 from an approximate value of 1.9°E to 5°E to reduce an ambiguity zone formed between each of said tracked units, whereby E is a maximum error said distance measured between two of said points P.sub.1, P.sub.2 or P.sub.3, a width of said ambiguity zone is equal to E, and a length of said ambiguity zone is less than 2°E.</p>	<p>91. The system for finding the target of claim 74, whereby an ambiguity zone is reduced by increasing a distance between each of points P.sub.1, P.sub.2 and P.sub.3, said distance is increased between two of said points P.sub.1, P.sub.2 or P.sub.3 from an approximate value of 1.9°E to 5°E to reduce an ambiguity zone formed between each of said tracked units, whereby E is a maximum error said distance measured between two of said points P.sub.1, P.sub.2 or P.sub.3, a width of said ambiguity zone is equal to E, and a length of said ambiguity zone is less than 2°E.</p>
<p>92. The system for finding the target of claim 91, whereby said system increases said distance measured between two of said points P.sub.1, P.sub.2 or P.sub.3 to a large distance reduces said ambiguity zone to a square having sides equal to E.</p>	<p>92. The system for finding the target of claim 91, whereby said system increases said distance measured between two of said points P.sub.1, P.sub.2 or P.sub.3 to a large distance reduces said ambiguity zone to a square having sides equal to E.</p>
<p>93. The system for finding the target of claim 74, whereby said monitoring unit is configured with a loop back mode, said loop back mode utilizes a value representing a data processing time correction, said value for data processing time correction is determined by sending an output signal to the input of a receiver from an output of the transmitter of said monitoring unit, whereby said processor of said monitoring unit sends test data to the input of an encoder and starts a timer, said processor receives said output signal from said input of said receiver and stops said timer, said processor compares said test data and said received signal for a validation, said processor computing a loop back elapsed time from said timer, and said processor further corrects said loop back elapsed time by adding either of said validation or said data processing time correction, or both.</p>	<p>93. The system for finding the target of claim 74, whereby said monitoring unit is configured with a loop back mode, said loop back mode utilizes a value representing a data processing time correction, said value for data processing time correction is determined by sending an output signal to the input of a receiver from an output of the transmitter of said monitoring unit, whereby said processor of said monitoring unit sends test data to the input of an encoder and starts a timer, said processor receives said output signal from said input of said receiver and stops said timer, said processor compares said test data and said received signal for a validation, said processor computing a loop back elapsed time from said timer, and said processor further corrects said loop back elapsed time by adding either of said validation or said data processing time correction, or both.</p>

Art Unit: 2617

<p>94. The system for finding the target of claim 74, whereby said monitoring unit is configured with a loop back mode, said loop back mode utilizes an output signal sent from an output of a transmitter sent to an attenuator connected directly to the input of a receiver of said monitoring unit.</p>	<p>94. The system for finding the target of claim 74, whereby said monitoring unit is configured with a loop back mode, said loop back mode utilizes an output signal sent from an output of a transmitter sent to an attenuator connected directly to the input of a receiver of said monitoring unit.</p>
<p>95. The system for finding the target of claim 74, wherein said monitoring unit includes an interface for audio communications and telemetry information exchange so as to communicate between each of master units in the system simultaneously or independently from the operation of a processor regarding said distance measurement.</p>	<p>95. The system for finding the target of claim 74, wherein said monitoring unit includes an interface for audio communications and telemetry information exchange so as to communicate between each of master units in the system simultaneously or independently from the operation of a processor regarding said distance measurement.</p>
<p>96. The system for finding the target of claim 74, wherein an interface provides communications between said monitoring unit and said tracked unit in the system simultaneously or independently from the distance measurement operation.</p>	<p>96. The system for finding the target of claim 74, wherein an interface provides communications between said monitoring unit and said tracked unit in the system simultaneously or independently from the distance measurement operation.</p>
<p>97. The system for finding the target of claim 96, whereby said interface provides full duplex audio communications and telemetry information exchange between said monitoring unit and said tracked unit, or between a plurality of said monitoring units in the system.</p>	<p>97. The system for finding the target of claim 96, whereby said interface provides full duplex audio communications and telemetry information exchange between said monitoring unit and said tracked unit, or between a plurality of said monitoring units in the system.</p>
<p>98. An integrated circuit for a wireless system for locating and tracking a subject or object, comprising a receiver; a transmitter; a microprocessor having a common clock as a source of synchronization; whereby said receiver and transmitter together define an active transponder and the integrated circuit is preferably a monolithic single die integrated circuit including said receiver, said transmitter, and said microprocessor; said transponder supplies predetermined ranging signals to a data processor portion of said microprocessor, said transponder includes an encoder for encoding data for transmission by said transmitter, and said a receiver includes a decoder circuit for receiving and decoding signals received from said antennae, and said a data processor for determining interval and position information, said data processor comprising a digital signal processor (DSP), a voltage stabilizer, and a battery supervisor; and an antenna for propagating said ranging said signal.</p>	<p>98. An integrated circuit for a wireless system for locating and tracking a subject or object, comprising a receiver; a transmitter; a microprocessor having a common clock as a source of synchronization; whereby said receiver and transmitter together define an active transponder and the integrated circuit is preferably a monolithic single die integrated circuit including said receiver, said transmitter, and said microprocessor; said transponder supplies predetermined ranging signals to a data processor portion of said microprocessor, said transponder includes an encoder for encoding data for transmission by said transmitter, and said a receiver includes a decoder circuit for receiving and decoding signals received from said antennae, and said a data processor for determining interval and position information, said data processor comprising a digital signal processor (DSP), a voltage stabilizer, and a battery supervisor; and an antenna for propagating said ranging said signal.</p>
<p>99. The circuit of claim 98, wherein said data information and ranging signals determined from input signals are coupled through a band pass filter, a distance measurement unit, and said decoder.</p>	<p>99. The circuit of claim 98, wherein said data information and ranging signals determined from input signals are coupled through a band pass filter, a distance measurement unit, and said decoder.</p>
<p>100. The circuit of claim 99, further including a microphone coupled to an input of a summing amplifier through a low frequency amplifier, said low frequency amplifier having compression/pre-emphasis, a low pass filter and an analog switch, said analog switch is operated by said DSP to enable a user to send voice</p>	<p>100. The circuit of claim 99, further including a microphone coupled to an input of a summing amplifier through a low frequency amplifier, said low frequency amplifier having compression/pre-emphasis, a low pass filter and an analog switch, said analog switch is operated by said DSP to enable a user to send voice</p>

Art Unit: 2617

communications when a monitoring or master unit is operating in a voice mode.

101. A method of a dynamic, mobile network for tracking and locating a plurality of monitoring units and targets T, comprising: tracking a primary target T with a primary monitoring unit having a predetermined range; determining when said target T moves out of said predetermined range; sending a ranging signal to at least one secondary monitoring unit within said predetermined range; receiving a reply ranging signal from at least one of said secondary monitoring unit; sending a request for a list of identified targets T to said secondary monitoring unit within a range of said secondary monitoring unit; receiving said list of identified targets T from said secondary monitoring unit; comparing said list of identified targets T to said primary target T; matching said primary target to one of said list of identified targets T from said secondary monitoring unit; and determining the location of the primary target from position information provided by said secondary monitoring unit.

102. A method of a dynamic, mobile network as in claim 101, comprising the additional step of: transferring tracking of said primary target to said secondary monitoring unit having said primary target in range.

103. A method for finding a target, comprising the steps of: determining a point P.sub.1 by having a user make an input to a monitoring unit; transmitting a ranging signal from said monitoring unit; receiving a reply ranging signal from a slave unit located on a subject or on an object at a point T, where said point T is located out of a range of said master unit; entering a homing mode on said monitoring unit; prompting said user to select a direction and having said user move in said direction along a path "Delta (1)" in a direction towards a point P.sub.2; actuating a step button on said monitoring unit to input once for each step taken by said user to generate reference points for a virtual triangulation calculation; prompting said user through said master unit to stop data input of said step button when said user reaches said point P.sub.2 determining using a processor of said monitoring unit whether the distance between subsequent points Delta (n) is equal or greater than (4-5)*E such that a value of said path Delta (1) is sufficiently large to minimize the a position ambiguity of said target T.

104. The method for finding a target of claim 103, further comprising the step of: prompting said user after reaching point P.sub.1 randomly to go either right or left from said Point P.sub.1 to a point P.sub.2 in a direction away from said target T.

105. The method for finding a target of claim 104, further comprising the step of: actuating a step button on said monitoring unit to input once for each step taken by said

communications when a monitoring or master unit is operating in a voice mode.

101. A method of a dynamic, mobile network for tracking and locating a plurality of monitoring units and targets T, comprising: tracking a primary target T with a primary monitoring unit having a predetermined range; determining when said target T moves out of said predetermined range; sending a ranging signal to at least one secondary monitoring unit within said predetermined range; receiving a reply ranging signal from at least one of said secondary monitoring unit; sending a request for a list of identified targets T to said secondary monitoring unit within a range of said secondary monitoring unit; receiving said list of identified targets T from said secondary monitoring unit; comparing said list of identified targets T to said primary target T; matching said primary target to one of said list of identified targets T from said secondary monitoring unit; and determining the location of the primary target from position information provided by said secondary monitoring unit.

102. A method of a dynamic, mobile network as in claim 101, comprising the additional step of: transferring tracking of said primary target to said secondary monitoring unit having said primary target in range.

103. A method for finding a target, comprising the steps of: determining a point P.sub.1 by having a user make an input to a monitoring unit; transmitting a ranging signal from said monitoring unit; receiving a reply ranging signal from a slave unit located on a subject or on an object at a point T, where said point T is located out of a range of said master unit; entering a homing mode on said monitoring unit; prompting said user to select a direction and having said user move in said direction along a path "Delta (1)" in a direction towards a point P.sub.2; actuating a step button on said monitoring unit to input once for each step taken by said user to generate reference points for a virtual triangulation calculation; prompting said user through said master unit to stop data input of said step button when said user reaches said point P.sub.2 determining using a processor of said monitoring unit whether the distance between subsequent points Delta (n) is equal or greater than (4-5)*E such that a value of said path Delta (1) is sufficiently large to minimize the a position ambiguity of said target T.

104. The method for finding a target of claim 103, rther comprising the step of: prompting said user after reaching point P.sub.1 randomly to go either right or left from said Point P.sub.1 to a point P.sub.2 in a direction away from said target T.

105. The method for finding a target of claim 104, further comprising the step of: actuating a step button on said monitoring unit to input once for each step taken by said user going to point P.sub.2 in a direction away from said

Art Unit: 2617

<p>user going to point P.sub.2 in a direction away from said target T to generate reference points for a virtual triangulation calculation.</p> <p>106. The method for finding a target of claim 105, further comprising the step of: prompting said user after reaching point P.sub.2 randomly to go either right or left from said Point P.sub.2 along a path "Delta (2)" to a point P.sub.3 in a direction away from said target T.</p> <p>107. The method for finding a target of claim 106,, further comprising the step of: actuating a step button on said monitoring unit to input once for each step taken by said user going to point P.sub.3 in a direction away from said target T to generate reference points for a virtual triangulation determination.</p> <p>108. The method for finding a target of claim 107, further comprising the step of: determining a Delta (n) using a current reference unit pre-programmed in said processor and calculating said Delta (n), which is equal to the difference (P(n-1)-current position).</p> <p>109. The method for finding a target of claim 108, further comprising the step of: prompting said user after determining said Delta (n) to move in a direction toward the target T.</p> <p>110. The method for finding a target of claim 109, further comprising the step of: prompting said user repeatedly along successive points P.sub.(n) in a direction toward the target T using virtual triangulation, and entering a homing mode upon approaching said target T after determining said Delta (n) to move in a direction toward the target T, wherein said master unit prompts said user.</p> <p>111. The method for finding a target of claim 110, further comprising the step of: requesting said slave unit to generate an audible signal upon approaching said target point T in said homing mode within a predetermined range, and generating an audible signal using said slave unit.</p> <p>108 (112). The method for finding a target of claim 111, further comprising the step of: requesting said slave unit to generate an audible signal upon approaching said target point T in said homing mode within a predetermined range, and generating an audible signal using said slave unit.</p> <p>109 (113). A method for finding a target, comprising the steps of: determining a point Pi by having a user make an input to a monitoring unit; transmitting a ranging signal from said monitoring unit; receiving a reply ranging signal from at least three stationary slave units located on subjects or on objects at a points T.sub.1, T.sub.2 and T.sub.3 within a predetermined range of said monitoring unit, whereby each of said points T.sub.1, T.sub.2 and T.sub.3 form a set of virtual coordinates</p>	<p>target T to generate reference points for a virtual triangulation calculation.</p> <p>106. The method for finding a target of claim 105, further comprising the step of: prompting said user after reaching point P.sub.2 randomly to go either right or left from said Point P.sub.2 along a path "Delta (2)" to a point P.sub.3 in a direction away from said target T.</p> <p>107. The method for finding a target of claim 106, further comprising the step of: actuating a step button on said monitoring unit to input once for each step taken by said user going to point P.sub.3 in a direction away from said target T to generate reference points for a virtual triangulation determination.</p> <p>108. The method for finding a target of claim 107, further comprising the step of: determining a Delta (n) using a current reference unit pre-programmed in said processor and calculating said Delta (n), which is equal to the difference (P(n-1)-current position).</p> <p>109. The method for finding a target of claim 108, further comprising the step of: prompting said user after determining said Delta (n) to move in a direction toward the target T.</p> <p>110. The method for finding a target of claim 109, further comprising the step of: prompting said user repeatedly along successive points P.sub.(n) in a direction toward the target T using virtual triangulation, and entering a homing mode upon approaching said target T after determining said Delta (n) to move in a direction toward the target T, wherein said master unit prompts said user.</p> <p>111. The method for finding a target of claim 110, further comprising the step of: requesting said slave unit to generate an audible signal upon approaching said target point T in said homing mode within a predetermined range, and generating an audible signal using said slave unit.</p> <p>108 (112). The method for finding a target of claim 111, further comprising the step of: requesting said slave unit to generate an audible signal upon approaching said target point T in said homing mode within a predetermined range, and generating an audible signal using said slave unit.</p> <p>109 (113). A method for finding a target, comprising the steps of: determining a point Pi by having a user make an input to a monitoring unit; transmitting a ranging signal from said monitoring unit; receiving a reply ranging signal from at least three stationary slave units located on subjects or on objects at a points T.sub.1, T.sub.2 and T.sub.3 within a predetermined range of said monitoring unit, whereby each of said points T.sub.1, T.sub.2 and T.sub.3 form a set of virtual coordinates relative to said point P.sub.1; and determining a location</p>
--	--

Art Unit: 2617

<p>relative to said point P.sub.1; and determining a location of said monitoring unit relative to said slave units using triangulation of points T.sub.1, T.sub.2 and T.sub.3 and said virtual coordinates relative to said point P.sub.1.</p> <p>110 (114). The method for finding a target of claim 109, further comprising the step of: transmitting a ranging signal from said monitoring unit to said slave units; receiving a reply ranging signal from each of said slave units; and prompting said user when said slave is out of a range of said monitoring unit.</p>	<p>of said monitoring unit relative to said slave units using triangulation of points T.sub.1, T.sub.2 and T.sub.3 and said virtual coordinates relative to said point P.sub.1.</p> <p>110 (114). The method for finding a target of claim 109, further comprising the step of: transmitting a ranging signal from said monitoring unit to said slave units; receiving a reply ranging signal from each of said slave units; and prompting said user when said slave is out of a range of said monitoring unit.</p>
<p>111 (115). The method for finding a target of claim 110, further comprising the step of: entering a homing mode on said monitoring unit; prompting said user to select a direction and having said user move in said direction along a path "Delta (1)" in a direction towards a point P.sub.2; determining a Delta (n) using a current reference unit pre-programmed in said processor and calculating said Delta (n), which is equal to the difference (P(n)-current position); and prompting said user after determining said Delta (n) to move in a direction toward the target T.</p> <p>112 (116). A method for finding a target, comprising the steps of: transmitting a ranging signal from a searching monitor unit M.sub.S; receiving a reply ranging signal from at least three stationary slave units located on subjects or on objects at a points P.sub.1, P.sub.2 and P.sub.3 within a predetermined range of said searching monitor unit M.sub.S, whereby each of said points P.sub.1, P.sub.2 and P.sub.3 form a set of virtual coordinates relative to said point Pi; determining said points P.sub.1 and P.sub.2 relative to said searching monitor unit M.sub.S having virtual coordinates X and Y using a processor of said searching monitor unit M.sub.S; determining a location of a mobile slave unit disposed on a subject forming a tracked target T, said target T having virtual coordinates are T.sub.y and T.sub.x; determining a location of said searching monitor unit M.sub.S relative to said tracked target T using said virtual coordinates formed by said stationary slave units and said virtual coordinates are M.sub.Sxy and S.sub.my for said searching monitor unit M.sub.S.</p> <p>113 (117). The method for finding a target of claim 112, further comprising the step of: determining a location of three stationary master units M.sub.1, M.sub.2 and M.sub.3, whereby said master unit M.sub.1 is separated from said master unit M.sub.2 by a distance D.sub.12, said master unit M.sub.1 is separated from said master unit M.sub.3 by a distance D.sub.13, said master unit M.sub.2 is separated from said master unit M.sub.3 by a distance D.sub.23.</p> <p>114 (118). The method for finding a target of claim 113, further comprising the step of: determining a distance Ms_R.sub.1, Ms_R.sub.2 and Ms_R.sub.3 [SM_R1,</p>	<p>111 (115). The method for finding a target of claim 110, further comprising the step of: entering a homing mode on said monitoring unit; prompting said user to select a direction and having said user move in said direction along a path "Delta (1)" in a direction towards a point P.sub.2; determining a Delta (n) using a current reference unit pre-programmed in said processor and calculating said Delta (n), which is equal to the difference (P(n)-current position); and prompting said user after determining said Delta (n) to move in a direction toward the target T.</p> <p>112 (116). A method for finding a target, comprising the steps of: transmitting a ranging signal from a searching monitor unit M.sub.s; receiving a reply ranging signal from at least three stationary slave units located on subjects or on objects at a points P.sub.1, P.sub.2 and P.sub.3 within a predetermined range of said searching monitor unit M.sub.s, whereby each of said points P.sub.1, P.sub.2 and P.sub.3 form a set of virtual coordinates relative to said point P.sub.1; determining said points P.sub.1 and P.sub.2 relative to said searching monitor unit M.sub.s having virtual coordinates X and Y using a processor of said searching monitor unit M.sub.s; determining a location of a mobile slave unit disposed on a subject forming a tracked target T, said target T having virtual coordinates are T.sub.y and T.sub.x; determining a location of said searching monitor unit M.sub.S relative to said tracked target T using said virtual coordinates formed by said stationary slave units and said virtual coordinates are M.sub.Sxy and S.sub.my for said searching monitor unit M.sub.S.</p> <p>113 (117). The method for finding a target of claim 112, further comprising the step of: determining a location of three stationary master units M.sub.1, M.sub.2 and M.sub.3, whereby said master unit M.sub.1 is separated from said master unit M.sub.2 by a distance D.sub.12, said master unit M.sub.1 is separated from said master unit M.sub.3 by a distance D.sub.13, said master unit M.sub.2 is separated from said master unit M.sub.3 by a distance D.sub.23.</p> <p>114 (118). The method for finding a target of claim 113, further comprising the step of: determining a distance Ms_R.sub.1, Ms_R.sub.2 and Ms_R.sub.3 [SM_R1,</p>

Art Unit: 2617

<p>SM_R2 and SM_R3] between said searching monitor unit Ms and said master units M.sub.1, M.sub.2 and M.sub.3, respectively.</p> <p>115 (119). The method for finding a target of claim 114, further comprising the step of: determining a distance T_R.sub.1, T_R.sub.2 and T_R.sub.3 between said target T and said master units M.sub.1, M.sub.2 and M.sub.3, respectively.</p> <p>116 (120). The method for finding a target of claim 115, further comprising the step of: determining position ambiguity between said master units M.sub.1, M.sub.2 and M.sub.3 and said distances D.sub.12, D.sub.13 and D.sub.23 so as to minimize ambiguity error between said target T distances T_R.sub.1, T_R.sub.2 and T_R.sub.3 and said master units M.sub.1, M.sub.2 and M.sub.3, respectively.</p> <p>117 (121). The circuit of claim 116, wherein said data information and ranging signals determined from input signals are coupled through a band pass filter, a distance measurement unit, and said decoder.</p>	<p>SM_R2 and SM_R3] between said searching monitor unit M.sub.s and said master units M.sub.1, M.sub.2 and M.sub.3 respectively.</p> <p>115 (119). The method for finding a target of claim 114, further comprising the step of: determining a distance T_R.sub.1, T_R.sub.2 and T_R.sub.3 between said target T and said master units M.sub.1, M.sub.2 and M.sub.3, respectively.</p> <p>116 (120). The method for finding a target of claim 115, further comprising the step of: determining position ambiguity between said master units M.sub.1, M.sub.2 and M.sub.3 and said distances D.sub.12, D.sub.13 and D.sub.23 so as to minimize ambiguity error between said target T distances T_R.sub.1, T_R.sub.2 and T_R.sub.3 and said master units M.sub.1, M.sub.2 and M.sub.3, respectively.</p> <p>117 (121). The circuit of claim 116, wherein said data information and ranging signals determined from input signals are coupled through a band pass filter, a distance measurement unit, and said decoder.</p>
---	---

Claim Objections

3. Claims 108-111 (second occurrence) and claims 112-117 are objected to because of the following informalities: These claims should be renumbered as claims 112-121. See claim pages 120-123. Appropriate correction is required.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to TEMICA M. BEAMER whose telephone number is (571)272-7797. The examiner can normally be reached on Monday-Thursday (alternate Fridays) 9:00am-5:00pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Charles Appiah can be reached on (571) 272-7904. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Temica M. Beamer/
Primary Examiner, Art Unit 2617